



## **Textile Trim**



THE **TOP** IN THE **CUTTING** OF **FABRICS**  
FOR THE TEXTILE INDUSTRY AND SOFT SIGNAGE

# TEXTILE TRIM IS THE ELECTRIC CUTTER

Designed and manufactured for the precise and efficient trimming of synthetic and natural fabrics, both in the textile industry and display graphics and soft signage markets.

Due to the availability of different cutting sizes, between 1.6 and 5.2 meters widths, and the bi-directional cutting system with variable speeds up to 0,5 m/sec, Textile Trim fits effectively in any production workflow, both in the traditional textile and the most advanced digital textile printing companies, calone or in combina in inkjet printers for textiles.

## OPTIONS / ACCESSORIES

extile Trim is supplied as a full-featured

## MAIN FEATURES

Textile trim is equipped with a sturdy stainless steel cutting head with an independent self-sharpening rotary blade that can be heated up to 325 °C, designed for trimming natural and synthetic fabrics.

The bi-directional cutting system is mounted on a reinforced cutting table and can operate at variable speeds up to 0.5 m/sec, allowing optimized cutting of different types of fabrics.

The illuminated working area, the pneumatic sheet-holder with foot pedal, the laser tracker and the reel-holder make the use of Textile Trim easy and intuitive for the operator, who can work hands-free and completely safe. Thanks to the floor-stand with adjustable feet, Textile Trim can be easily placed in any production environment.

**Document imaging**  
by Charles Kieffer Group

**Tél.** +352 26 380 1    **Fax** +352 26 380 380  
[sales@ck-group.lu](mailto:sales@ck-group.lu)  
 2, rue Léon Laval - Z.A. Am Bann  
 L-3372 Leudelange  
[ck-group.lu](http://ck-group.lu)



## DATASHEET

	165	340	520
Cutting width	1650 mm	3400 mm	5200 mm
Carriage speed	Max. 0,5 m/sec. (1.64 foot/sec.)		
Max. Cutting thickness	mm 7 / (0.28")		
Width	2500 mm	4210 mm	6070 mm
Depth	580 mm		
Height with stand	1120 mm		
Voltage	230/240 V -50 Hz / 110 V -60 Hz		
Electric consumption	Max. 2,1A 500 W	Max. 2,6A 600 W	Max. 3A 700 W
Air pressur	6/7 Bar		
Cutting blade temperature	up to 325°C (617°F)		
Weight	105 Kg	200 Kg	300 KG

\* The manufacturers reserves the right to change technical and aesthetical specifications without notice.