

# REVAMP2600

2-channel power amplifier, 2 x 600 watts @ 4 ohms



REVAMP2600 is a professional 2-channel power amplifier with 2 x 840 watts output power @ 4 ohms. The digital signal processor inside operates with one simple push button at the back of the unit to select an operating mode (10 presets) what makes this amplifier the ideal multipurpose tool for applications where you need a lot of power in two different zones like fitness centres or stereo applications.

The amplifier contains an intelligent variable speed cooling fan. The REVAMP2600 also temporally decreases the output power to a safe limit whenever a thermal overload occurs (indicated by a LED light on the front panel). The very intuitive front display shows what is going on with one blink of an eye. Thanks to our own designed automatic protection system (patent pending) with smart use of a compressor/limiter topology we bring our power supply to an unexpected high level! This manifests itself in a great dynamic power with an unseen musicality and exceptional dynamic sound.

There are 9 presets available which can be selected by the button at the back of the unit. An example of a preset is the combination CH1 subwoofer and CH2 trafo load. In this example you have a low-pass filter for increased stability when using 100 volt transformers on the output, allowing you to use 100 volt speakers as top speakers combined with a standard low impedance subwoofer. With the other presets channels can be linked, high pass filters can be applied to a channel...

Ease of use, high-tech, reliability and big output power has never been as cleverly combined as in this REVAMP2600 amplifier.

## TECHNICAL SPECIFICATIONS

dynamic output power 4 ohms in watts	2 x 840	RMS output power 4 ohms in watts	2 x 600
dynamic output power 8 ohms in watts	2 x 420	RMS output power 8 ohms in watts	2 x 300
minimum impedance load per channel in ohms	4	power consumption (max) in watts	1840
19" (483 mm wide) rack mounting	yes	height- rack units (1U=44 mm) in U	2
depth (build in) in mm	334	depth (incl front) in mm	340
power supply	230 VAC	power supply technology	toroidal transformer
output channels	2	line input balanced	2
line input unbalanced	2	channel separation	> 67 dB @ 1 kHz
power amp topology	class-H	frequency response (in Hz)	10 - 24 k
cooling system	fan	applicable low impedance	yes
Net weight product (kg)	12.10		

MORE PICTURES



ACCESSORIES



**CSP**

(H) Speakon Connector MAle

**CK**

Document  
imaging

by Charles Kieffer Group

**Tél.** +352 26 380 1 **Fax** +352 26 380 380  
sales@ck-group.lu

2, rue Léon Laval - Z.A. Am Bann  
L-3372 Leudelange

**ck-documentimaging.lu**