

# SKM200-D-US

## Digital Handheld Transmitter



The SKM 200-D-US handheld transmitter may be the easiest way to address your audience. Should a participant have a question, simply hand the microphone to them and all participants will hear clearly! The transmitter is easy to operate and offers a rugged design for everyday use. The microphone effectively attenuates unwanted background noise to ensure clear, reliable communication to all of your listeners. A convenient backlit display allows the user to view the active channel, as well as battery status. The included BA2015 G2 rechargeable battery offers up to 8 hours of use and charges in about 3.5 hours with the EZL2020-20L charger.

### About the Tourguide 2020 Series

The Tourguide 2020 series is the first digital RF wireless tour guide system in the ISM band, offering excellent audio quality and extremely reliable, interference-free communication. Designed for easy set-up and operation, this system offers a high degree of flexibility with six available audio channels, making it an ideal choice for almost any guided tour application! Other system components include a small bodypack transmitter, SK 2020-D-US, with your choice of microphone (ordered separately); lightweight stethoset receivers, HDE 2020-D-US; and a portable, convenient carrying case with charger, EZL2020-20L.

### KEY FEATURES

- Digital RF wireless transmission
- 6 channels in the license-free ISM frequency band (926-928 MHz)
- Rugged housing for everyday use
- Ideal for use in noisy environments
- Backlit display indicates selected channel and battery status
- Rotatable end cap for on/off, mute, and menu settings
- Up to 8 hours of use with the BA2015G2 rechargeable battery

### TECHNICAL DATA

Modulation	2-FSK
RF frequency range	926 -928 MHz
Number of channels	6
Frequency response	100 – 7,000 Hz
RF output power	1 mW
Signal-to-noise ratio	> 65 dB(A)
Total harmonic distortion	≤ 1%
Pick-up pattern	Cardioid
Transducer principle	Dynamic
Operating time (rech. batt. pack)	8 hours
Power supply	BA 2015 (2.4 V); 2 AA (1.5 V)
Operating temperature	0 - 50°C
Weight incl. rechargeable batt. pack	14.82 oz.
Range	80 ft. indoors, 160 ft. outdoors

# SKM2020-D-US

## Digital Handheld Transmitter

### APPLICATIONS:

---

The SKM2020-D-US offers a high degree of flexibility with six available audio channels, making it an ideal choice for almost any guided tour, assistive listening, language transmission and more!

### ARCHITECT SPECS

---

The transmitter must utilize the ISM band frequencies of 926 – 928 MHz for transmission of up to six audio channels, with an AF frequency response of 100–7,000 Hz. It must accept a rechargeable battery or 2 AA batteries. It must feature a rotatable end cap for access to on/off, mute, menu up/down, and set buttons. It must have a backlit display indicating signal source, source level, selected channel, battery status and lock mode. It must be easily configured via set and menu up/down buttons.



Document  
imaging

by Charles Kieffer Group

**Tél.** +352 26 380 1 **Fax** +352 26 380 380  
sales@ck-group.lu

2, rue Léon Laval - Z.A. Am Bann  
L-3372 Leudelange

**ck-documentimaging.lu**