

ATLANTIC 1650

New Hot & Cold laminator

THERMAL LAMINATION

- Use of thermal encapsulation films up to 320 microns

COLD LAMINATION

- Single side lamination with or without waste paper
- Simultaneous single side lamination and adhesive mounting
- Encapsulation with cold film in one run
- Application tape
- Colour background using colour vinyl
- Mounting onto boards up to 50 mm (2") thickness



Speed up to 6,20 m/mn (21 ft/mn)
Mounting up to 50 mm (2") thick.
Hi-capacity hot and cold laminator up to 140°C (280°F)
Working width 165 cm (65")



Specifications

 Mounting up to 50 mm (2")	 10 speed	 Diameter 23 cm (9"), film reel 100 m (110 yd)	<h3>Atlantic 1650</h3>
Maximum thickness document + board	50 mm (2")		
Maximum working width	171 cm (67")		
Maximum film width	165 cm (64")		
Maximum length of the film reels	100 m (maximum diameter 23 cm/9")		
Diameter of the rollers	maximum 120 mm (4.7")		
Temperature	independant heat on top and bottom up to 140°C		
Heating time from 20°C to 100°C	30 mn		
Number of self blocking shaft delivered	5 + 1 unwinding shaft		
Adjustable speed m/mn	from 0,3 to 6,3		
Adjustable speed ft/mn	from 0,9 to 21		
Power W	3600		
Voltage	230 V / 50-60 Hz		
Amperage	16A/230 V		
Dimensions of the machine	(cm) (inch)	W 206 x D 82 x H 153 W 81" x D 32" x H 60"	
Net weight of the machine	300 kg		
Shipping dimensions of the machine	(cm) (inch)	W 213 x P93 x H 170 L 84" x P 37" x H 66"	
Machine weight for shipping	370 kg		
Warranty	1 year		
Made in France, CE certified in compliance with the Machine and the Electromagnetic Compatibility Directives CEM.			

Roll to Roll system delivered as standard with the machine.

CK Document imaging
by Charles Kieffer Group

Tél. +352 26 380 1 Fax +352 26 380 380
 sales@ck-group.lu
 2, rue Léon Laval - Z.A. Am Bann
 L-3372 Leudelange
 ck-documentimaging.lu



RoHS

